



VIYY.EX15750 Fittings, Accessory

[Page Bottom](#)

Fittings, Accessory

[See General Information for Fittings, Accessory](#)

MASON INDUSTRIES INC

EX15750

350 RABRO DR
HAUPPAUGE, NY 11788 USA

Flexible joint fittings, Model VGN grooved, 2, 2-1/2 and 3 in. sizes, for pressures to 300 psig.

Model VGN grooved, 4, 5, 6 and 8 in. sizes, for pressures to 175 psig.

Model VCPSB female sweat ends, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 and 4 in. sizes, for pressures to 175 psig.

Model GN grooved, 2, 2-1/2, 3, 4, 5, 6 and 8 inch sizes, for pressures to 175 psig.

Model CPSB female sweat ends, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 and 4 inch sizes, for pressures to 175 psig.

Model FFL and FFLSS flanged, 2, 2-1/2, 3, 4, 5, 6 and 8 inch sizes, for pressures to 175 psig.

Model FFL2B300 flanged, 2, 2-1/2, 3, 4, 5 and 6 inch sizes, for pressures to 300 psig.

Model FFL2B300 flanged, 8 inch size, for pressures to 175 psig.

Model FFLPN10, FFLPN16, FFLPN20 and FFLPN25 flanged, 2, 2-1/2, 3, 4, 5, 6 and 8 inch sizes, for pressures to 175 psig.

Model VFL flanged, 2, 2-1/2, 3, 4, 5, 6 and 8 inch sizes, for pressures to 175 psig.

Model MN threaded, 2, 2-1/2, 3 and 4 inch sizes, for pressures to 175 psig.

Model VMN threaded, 2, 2-1/2, 3 and 4 inch sizes, for pressures to 175 psig.

Model VWN welded, 2, 2-1/2, 3, 4, 5, 6 and 8 inch sizes, for pressures to 175 psig.

Model GNF grooved/flanged 2, 2-1/2, 3, 4, 5, 6 and 8 inch sizes, for pressures to 175 psig.

Suitable for use in dry pipe systems for temperatures to -40F.

[Last Updated](#) on 2011-08-01

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2011 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An Independent organization working for a safer world with integrity, precision and knowledge.





VIYY7.EX15750
Fittings, Accessory Certified for Canada

[Page Bottom](#)

Fittings, Accessory Certified for Canada

[See General Information for Fittings, Accessory Certified for Canada](#)

MASON INDUSTRIES INC
350 RABRO DR
HAUPPAUGE, NY 11788 USA

EX15750

Flexible joint fittings, Model VGN grooved, 2, 2-1/2 and 3 in. sizes, for pressures to 2068 kPa.

Model VGN grooved, 4, 5, 6 and 8 in. sizes, for pressures to 1210 kPa.

Model VCPSB female sweat ends, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 and 4 in. sizes, for pressures to 1210 kPa.

Model GN grooved, 2, 2-1/2, 3, 4, 5, 6 and 8 inch sizes, for pressures to 1210 kPa.

Model CPSB female sweat ends, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 and 4 inch sizes, for pressures to 1210 kPa.

Model FFL and FFLSS flanged, 2, 2-1/2, 3, 4, 5, 6 and 8 inch sizes, for pressures to 1210 kPa.

Model FFL2B300 flanged, 2, 2-1/2, 3, 4, 5 and 6 inch sizes, for pressures to 2068 kPa.

Model FFL2B300 flanged, 8 inch size, for pressures to 1210 kPa.

Model FFLPN10, FFLPN16, FFLPN20 and FFLPN25 flanged, 2, 2-1/2, 3, 4, 5, 6 and 8 inch sizes, for pressures to 1210 kPa.

Model VFL flanged, 2, 2-1/2, 3, 4, 5, 6 and 8 inch sizes, for pressures to 1210 kPa.

Model MN threaded, 2, 2-1/2, 3 and 4 inch sizes, for pressures to 1210 kPa.

Model VMN threaded, 2, 2-1/2, 3 and 4 inch sizes, for pressures to 1210 kPa.

Model VWN welded, 2, 2-1/2, 3, 4, 5, 6 and 8 inch sizes, for pressures to 1210 kPa.

Suitable for use in dry pipe systems for temperatures to -40C.

Model GNF grooved/flanged 2, 2-1/2, 3, 4, 5, 6 and 8 inch sizes, for pressures to 1210 kPa.

[Last Updated](#) on 2011-08-01

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2011 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

